


Systems

fermacell® CLT/X-LAM Building in Timber



1. Wall

1.1 CLT/X-LAM

fermacell®

System-Specification	Systemdrawing	Wall Thickness	CLT / X-LAM	Facings	Insulation Thickness/Density
		[mm]	[mm]	[mm]	[mm]/[kg/m³]
1 HTM 11		≥ 100	≥ 80	10	-
1 HTM 23		≥ 100	≥ 80	10	-
1 HTM 24		≥ 130	≥ 80	2 × 12,5	-
1 HTM 21		≥ 145	≥ 120	12,5	-
1 HTM 22		≥ 172	≥ 120	12,5 one side traverse -resilient bar	Glass-wool
1 HTM 34		≥ 130	≥ 80	2 × 12,5	-
1 HTM 32		≥ 145	≥ 120	12,5	-
1 HTM 33		≥ 172	≥ 120	12,5 one side traverse -resilient bar	Glass-wool
1 HTM 31		≥ 180	≥ 120	2 × 15	-
1 HTM 41		≥ 156	≥ 120	18	-
1 HTM 42		≥ 180	≥ 120	2 × 15	-

* arithmetically acc. Soundinsulationsoftware NSUL, Version v.8.0.3

** based on EN 13501-2

Applied Load	Wall Weight	Sound Insulation R_w	Sound Insulation $D_{n,f,W}^{(12)}$	Fire Rating according EN 13501-2 (EN 1365-1)	Classification Report
[kN/m]	[kg/m ²]	[dB]	[dB]		
160	≥ 60	$R_w \geq 37$ {-1;-3}* Pb.- Nr.: 04-001031	-	REI30	KB 3.2/19-354-3 -Covering: K ₂ 10 -PC10069 -T _{max. 10 minutes} : 112 °C
40	≥ 60	$R_w \geq 37$ {-1;-3}* Pb.- Nr.: 04-001030	-	REI60	KB 3.2/19-354-3 -Covering: K ₂ 10 -PC10069 -T _{max. 10 minutes} : 112 °C
160	≥ 96	$R_w \geq 41$ {-1;-3}* Pb.- Nr.: 04-001029	-	REI60	KB 3.2/19-354-4 -Covering: K ₂ 30 -PCA10402A -T _{max. 30 minutes} : 115 °C
200	≥ 87	≥ 40 {-1;-3}* Pb.- Nr.: 04-001028	-	REI60	KB 3.2/16-279-3 -Covering: K ₂ 10 -PC10069 -T _{max. 10 minutes} : 112 °C
200	≥ 89	$R_w \geq 53$ {-4;-11}* Pb.- Nr.: 04-001027	-	REI60	KB 3.2/16-388-2 -Covering: K ₂ 10 -PC10069 -T _{max. 10 minutes} : 112 °C
40	≥ 96	$R_w \geq 41$ {-1;-3}* Pb.- Nr.: 04-001026	-	REI90	KB 3.2/19-354-4 -Covering: K ₂ 30 -PCA10402A -T _{max. 30 minutes} : 115 °C
120	≥ 87	≥ 40 {-1;-3}* Pb.- Nr.: 04-001024	-	REI90	KB 3.2/16-279-3 -Covering: K ₂ 10 -PC10069 -T _{max. 10 minutes} : 112 °C
120	≥ 89	$R_w \geq 53$ {-4;-11}* Pb.- Nr.: 04-01023	-	REI90	KB 3.2/16-388-2 -Covering: K ₂ 10 -PC10069 -T _{max. 10 minutes} : 112 °C
200	≥ 129	≥ 44 {-1;-3}* Pb.- Nr.: 04-001021	-	REI90	KB 3.2/15-369-4 (Covering: K ₂ 45)**
120	≥ 100	≥ 41 {-1;-2}* Pb.- Nr.: 04-001022	-	REI120	KB 3.2/15-369-3 -Covering: K ₂ 30 -PCA10168 -T _{max. 30 minutes} : 153 °C
150	≥ 129	≥ 44 {-1;-32}* Pb.- Nr.: 04-001021	-	REI120	KB 3.2/15-369-4 (Covering: K ₂ 45)**

1. Wall

1.1 CLT/X-LAM

Firepanel A1

System Specification	Systemdrawing	Wall Thickness	CLT / X-LAM	Facings	Insulation Thickness/Density
		[mm]	[mm]	[mm]	[mm]/[kg/m³]
1 HTM 21 A1		≥ 100	≥ 80 mm	10	-
1 HTM 41 A1		≥ 235	≥ 80 mm	12,5 [CW50] 10	40/40

fermacell® - cavity wall

System Specification	Systemdrawing	Wall Thickness	CLT / X-LAM	Facings	Insulation Thickness/Density
		[mm]	[mm]	[mm]	[mm]/[kg/m³]
1 HTM 12		≥ 190	≥ 2 × 80 mm 10 mm cavity 100 mm cavity	10	- 80/10
1 HTM 25		≥ 190	≥ 2 × 80 mm 10 mm cavity 100 mm cavity	10	- 80/10
1 HTM 26		≥ 220	≥ 2 × 80 mm 10 mm cavity 100 mm cavity	2 × 12,5	- 80/18
1 HTM 27		≥ 275	≥ 2 × 120 mm 10 mm cavity 100 mm cavity	12,5	- 80/10
1 HTM 35		≥ 220	≥ 2 × 80 mm 10 mm cavity 100 mm cavity	2 × 12,5	- 80/18

* arithmetically acc. Soundinsulationsoftware INSUL, Version v.8.0.3

Applied Load	Wall Weight	Sound Insulation R_w	Sound Insulation $D_{n,f,W}^{(12)}$	Fire Rating according EN 13501-2 (EN 1365-1)	Classification Report
[kN/m]	[kg/m ²]	[dB]	[dB]		
45	≥ 61	$R_w \geq 37$ (-1;-3)* Pb.- Nr.: 04-01020	-	REI60	N° CSI1958FR -Covering: K ₂ 10 -PCA10080 -T _{max. 10 minutes} : 135 °C
45	≥ 95	$R_w \geq 71$ (-6;-14)* Pb.- Nr.: 04-01019	-	REI120	N° CSI1959FR

Applied Load	Wall Weight	Sound Insulation R_w	Sound Insulation $D_{n,f,W}^{(12)}$	Fire Rating according EN 13501-2 (EN 1365-1)	Classification Report
[kN/m]	[kg/m ²]	[dB]	[dB]		
160 each wall side	≥ 96	$R_w \geq 49$ (-3;-11)* Pb.- Nr.: 04-01017	-	REI30	KB 3.2/19-354-3 -Covering: K ₂ 10 -PC10069 -T _{max. 10 minutes} : 112 °C
		$\underline{R_w \geq 69}$ (-2;-6)* Pb.- Nr.: 04-01018			
40 each wall side	≥ 96	$R_w \geq 49$ (-3;-9)* Pb.- Nr.: 04-01015	-	REI60	KB 3.2/19-354-3 -Covering: K ₂ 10 -PC10069 -T _{max. 10 minutes} : 112 °C
		$\underline{R_w \geq 69}$ (-2;-6)* Pb.- Nr.: 04-01016			
160 each wall side	≥ 132	$R_w \geq 54$ (-3;-11)* Pb.- Nr.: 04-01014	-	REI60	KB 3.2/19-354-4 -Covering: K ₂ 30 -PCA10402A -T _{max. 30 minutes} : 115 °C
		$\underline{R_w \geq 74,5}$ (-2;-4) Pb.- Nr.: 04-00961			
200 each wall side	≥ 143	$R_w \geq 55$ (-5;-12)* Pb.- Nr.: 04-01012	-	REI60	KB 3.2/16-279-3 -Covering: K ₂ 10 -PC10069 -T _{max. 10 minutes} : 112 °C
		$\underline{R_w \geq 75}$ (-2;-6)* Pb.- Nr.: 04-01013			
40 each wall side	≥ 132	$R_w \geq 54$ (-4;-11)* Pb.- Nr.: 04-01011	-	REI90	KB 3.2/19-354-4 -Covering: K ₂ 30 -PCA10402A -T _{max. 30 minutes} : 115 °C
		$\underline{R_w \geq 74,5}$ (-2;-4) Pb.- Nr.: 04-0961			

1. Wall

1.1 CLT/X-LAM

fermacell® - cavity wall

System Specification	Systemdrawing	Wall Thickness	CLT / X-LAM	Facings	Insulation Thickness/Density
		[mm]	[mm]	[mm]	[mm]/[kg/m³]
1 HTM 36		≥ 275	≥ 2 × 120 mm 10 mm cavity 100 mm cavity	12,5	- 80/10
1 HTM 37		≥ 310	≥ 2 × 120 mm 10 mm cavity 100 mm cavity	2×15	- 80/18
1 HTM 43		≥ 286	≥ 2 × 120 mm 10 mm cavity 100 mm cavity	18	- 80/18
1 HTM 44		≥ 310	≥ 2 × 120 mm 10 mm cavity 100 mm cavity	2×15	- 80/18

* arithmetically acc. Soundinsulationsoftware INSUL, Version v.8.0.3

Firepanel A1 - cavity wall

System Specification	Systemdrawing	Wall Thickness	CLT / X-LAM	Facings	Insulation Thickness/Density
		[mm]	[mm]	[mm]	[mm]/[kg/m³]
1 HTM 22 A1		≥ 100	≥ 2 × 80 mm 10 mm cavity 100 mm cavity	10	- 80/10

* arithmetically acc. Soundinsulationsoftware INSUL, Version v.8.0.3

** based on EN 13501-2

Applied Load	Wall Weight	Sound Insulation R_w	Sound Insulation $D_{n,f,W}^{(12)}$	Fire Rating according EN 13501-2 (EN 1365-1)	Classification Report
[kN/m]	[kg/m ²]	[dB]	[dB]		
120 each wall side	≥ 143	$R_w \geq 55$ (-5;-12)* Pb.- Nr.: 04-01008	—	REI90	KB 3.2/16-279-3 -Covering: K ₂ 10 -PCA10069 -T _{max.} 10 minutes: 112 °C
		$\underline{Rw \geq 75}$ (-2;-6)* Pb.- Nr.: 04-01009			
200 each wall side	≥ 185	$R_w \geq 60$ (-5;-13)* Pb.- Nr.: 04-01007	—	REI90	KB 3.2/15-369-4 (Covering: K ₂ 45)**
		$\underline{Rw \geq 74,5}$ (-2;-4) Pb.- Nr.: 04-00961			
120 each wall side	≥ 100	$R_w \geq 57$ (-5;-12)* Pb.- Nr.: 04-01006	—	REI120	KB 3.2/15-369-3 (Covering: K ₂ 30) -Covering: K ₂ 30 -PCA10168 -T _{max.} 30 minutes: 153 °C
		$\underline{Rw \geq 77}$ (-2;-6)* Pb.- Nr.: 04-01010			
150 each wall side	≥ 185	$R_w \geq 60$ (-6;-15)* Pb.- Nr.: 04-01003	—	REI120	KB 3.2/15-369-4 (Covering: K ₂ 45)**
		$\underline{Rw \geq 74,5}$ (-2;-4) Pb.- Nr.: 04-00961			

Applied Load	Wall Weight	Sound Insulation R_w	Sound Insulation $D_{n,f,W}^{(12)}$	Fire Rating according EN 13501-2 (EN 1365-1)	Classification Report
[kN/m]	[kg/m ²]	[dB]	[dB]		
45 each wall side	≥ 97	$R_w \geq 49$ (-3;-9)* Pb.- Nr.: 04-01004	—	REI60	N° CSI1958FR -Covering: K ₂ 10 -PCA10080 -T _{max.} 10 minutes: 135 °C
		$\underline{Rw \geq 69}$ (-2;-15)* Pb.- Nr.: 04-01005			

1. Wall

1.1 CLT/X-LAM

fermacell® - firewall

System Specification	Systemdrawing	Wall Thickness [mm]	CLT / X-LAM [mm]	Facings [mm]	Insulation Thickness/Density [mm]/[kg/m³]
4 HTM 32		≥ 146	≥ 80	15 + 18	-
4 HTM 33		≥ 280	≥ 80	innen 15 + 18 außen 160 mm STEICOprotect L dry + 6 mm STEICOsecure base	-

* arithmetically acc. EN12354-1:2000, S. 28

fermacell® - cavity firewall

System Specification	Systemdrawing	Wall Thickness [mm]	CLT / X-LAM [mm]	Facings [mm]	Insulation Thickness/Density [mm]/[kg/m³]
4 HTM 31		≥ 236	≥ 2 × 80 mm 10 mm cavity 100 mm cavity	18 + 15	- 80/18

* arithmetically acc. Soundinsulationsoftware INSUL, Version v.8.0.3


Applied Load max. Stress sc,0,d,R90	Wall Weight	Sound Insulation R_w	Sound Insulation $D_{n,f,w}^{(12)}$	Fire Rating according EN 13501-2 (EN 1365-1)	Classification Report
[N/mm ²]	[kg/m ²]	[dB]	[dB]		
3,0	≥ 117	$Rw \geq 42$ (-1;-2) Pb.- Nr.: 04-01002	≥ 61	REI 90-M	KB 3.2/16-325-1 -Covering: K ₂ 60 -PC10082 -T _{max. 60 minutes} : 104 °C
2,5	≥ 123	$Rw \geq 36$ (-1;-5) Pb.- Nr.: 04-00879	≥ 61	REI 90-M	KB 3.2/15-222-2 [Covering from inside: K ₂ 60] -Covering: K ₂ 60 -PC10082 -T _{max. 60 minutes} : 104 °C

Applied Load max. Stress sc,0,d,R90	Wall Weight	Sound Insulation R_w	Sound Insulation $D_{n,f,w}^{(12)}$	Fire Rating according EN 13501-2 (EN 1365-1)	Classification Report
[N/mm ²]	[kg/m ²]	[dB]	[dB]		
3 each wall side	≥ 152	$R_w \geq 56$ (-5;-13)* <hr/> $Rw \geq 74,5$ (-2;-4) Pb.- Nr.: 04-00961	-	REI 90-M	KB 3.2/16-325-1 [Covering: K ₂ 60] -Covering: K ₂ 60 -PC10082 -T _{max. 60 minutes} : 104 °C

2. Covering

2.1 Classification of wall and ceiling coverings for fire protection ability

fermacell®

Coverings designated EN 13501-2	K _z 10	K _z 30
Facings	10 mm	2x10 alternative 18 mm
		
Classification Report	PC 10069	Classification Report KB III/B-07-059
		
Flooring **	-	-

* based on EN 13501-2

** based on German building regulation

K _z 45*	K _z 60
2×15	15+18 mm alternative 2×18 mm alternative 3×12,5 mm alternative 12,5 mm+60 mm ETICS [StoTherm Classic L]
Test Report	PB III/B-03-271
	Classification Report PCA 10081
	Classification Report PCA 10107
	Classification Report PCA 10%-%
	2 E 35 fermacell® Flooring Element 2×12,5 mm fermacell® Gypsum Fibreboard + 20 mm mineral wool


A covering designated K2 is an encapsulation performance which for the classification period (10 min, 30 min or 60 min) provides the prescribed protection for the materials behind the covering.

During this time the mean temperature measured on the unexposed side of the covering not exceed the initial temperature by more than 250 K and the maximum temperature measured at any point of these sides not exceed the initial temperature by more than 270 K.


The classification protect the unexposed side of the covering against charring/burning during the time of classification.

(see also EN13501-2)

1 HTM 41



4 HTM 32








3. Ceiling

3.1 CLT/X-LAM


fermacell® Flooring Elements

	CLT/X-LAM	REI 60 (b→a)** REI 90 (b→a)** <i>CLT 140 C5s CLT 160 C5s*</i> <i>Load: 5 kN/m² Load: 6 kN/m²</i> <i>Span: 5 m Span: 5 m</i>	 Bare floor $R_w = 39 \text{ dB}$ $L_{n,w} = 85 \text{ dB}$
---	------------------	---	---

System drawing	Construction	Constr. height	Sound insulation		Area of application
			[mm]	[dB]	
	2 E 22 (2 × 12,5 mm fermacell® Gypsum Fibreboards) on 30 mm fermacell™ Honeycomb Insulation on 20 mm Floorrock GP on 60 mm EPS 150 kPa on 30 mm fermacell™ Honeycomb Insulation	305	46,0 (+2 +8)	67,8 (-4 -12 -9 -21)	1
	2 E 22 (2 × 12,5 mm fermacell® Gypsum Fibreboards) on 30 mm fermacell™ Honeycomb Insulation on 80 mm Schneider 140 kPa on 30 mm fermacell™ Honeycomb Insulation	305	48,4 (+1 +5)	68,3 (-4 -11 -9 -22)	1
	2 E 35 (2 × 12,5 mm fermacell® Gypsum Fibreboards + 20 mm Mineral Wool) on 2 × 30 mm fermacell™ Honeycomb Insulation	245	50,2 (+0 +3)	66,9 (-3 -10 -8 -20)	1
	2 E 35 (2 × 12,5 mm fermacell® Gypsum Fibreboards + 20 mm Mineral Wool) on 30 mm fermacell™ Honeycomb Insulation	215	51,8 (+1 +4)	64,2 (-4 -11 -9 -20)	1
	2 E 22 (2 × 12,5 mm fermacell® Gypsum Fibreboards on 20 mm Steico Therm sd on 30 mm fermacell™ Honeycomb Insulation	215	53,6 (+1 +3)	64,1 (-4 -11 -9 -20)	1

* * ETA-14/0349

fermacell® Flooring Elements



System drawing	Construction	Constr. height	Sound insulation	Area of application
		[mm]	[dB]	
	2 E 35 (2 × 12,5 mm fermacell® Gypsum Fibreboards + 20 mm Mineral Wool) on 2 × 30 mm fermacell™ Honeycomb Insulation with 140 mm CLT with 27 mm flexibly suspended + Mineral Wool on 3 × 12,5 mm fermacell® Gypsum Fibreboards	309,5	38,7 (+2 +21)	75,8 (-7 -16 -22 -35)
	2 E 35 (2 × 12,5 mm fermacell® Gypsum Fibreboards + 20 mm Mineral Wool) on 2 × 30 mm fermacell™ Honeycomb Insulation with 140 mm CLT with 27 mm flexibly suspended + Mineral Wool on 2 × 12,5 mm fermacell® Gypsum Fibreboards	297	41,3 (+2 +18)	74,2 (-9 -18 -21 -34)
	2 E 35 (2 × 12,5 mm fermacell® Gypsum Fibreboards + 20 mm Mineral Wool) on 2 × 30 mm fermacell™ Honeycomb Insulation with 140 mm CLT with 27 mm flexibly suspended + Mineral Wool on 2 × 12,5 mm fermacell® Gypsum Fibreboards	284,5	50,0 (+4 +10)*	74,2 (-9 -18 -21 -34)*

* internal review and investigation

You will find the latest version of this brochure in digital form on our website. Technical modifications subject to changes. Last updated 02/2021

The most recent edition applies. Should you require additional information, please contact our customer service.

©2021 James Hardie Europe GmbH.

™ and ® denote registered and unregistered trademarks of James Hardie Technology Ltd. and James Hardie Europe GmbH.

James Hardie Europe GmbH

Bennigsen-Platz 1

D-40474 Düsseldorf

www.fermacell.com

Technical customer information (freecall)

phone 08003864001

e-Mail fermacell@jameshardie.de

Service-Center (order management)

phone +49 211 54236-200

fax +49 211 54236-299

e-mail auftraege@jameshardie.com

fer-600-00011/02.2021

